

Type Approval Certificate



This is to certify that the undemoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 47 924 - 03 HH

Company DK Tech. Corporation

7, Golden root-ro 129 beon-gil Juchon-Myeon,
Gimhae-City, Gyeongnam 621-842, REPUBLIC OF KOREA

Product Description PIPE UNION

Type BITE TYPE TUBE FITTING

Environmental Category None

Technical Data /
Range of Application

Material:	Brass		
Temperature range:	- 55 [°C] to + 175 [°C]		
Elastomer seals:	NBR	FPM	PTFE
Temperature range [°C]:	- 40 to +100	- 20 to +175	- 55 to +175
Pipe O.D. [mm]:	4 to 5	6 to 22	25
Nom. Press. PN [bar]:	250	210	170

The pressure reduction for the specified temperature has to be observed.

LIMITATIONS:

The Bite Type tube fittings made of brass may be used in piping systems where pressure pulsation is not expected. Pipe unions with elastomer seals are not approved within machinery spaces for the use in fuel-, lubricating-, hydraulic oil, sea water and bilge piping systems. Threaded bulkhead pipe unions are not approved through watertight bulkheads.

Test Standard VI-7-8 Test Requirements for Components and Systems of Mechanical Engineering and Offshore Technology

Documents Test reports of tests, Catalogue No. 02-2

Remarks The selection of the pipe unions and the installation has to be in accordance with the instructions of the manufacturer.

Valid until 2019-03-06

Page 1 of 1

File No. II.C.05

Hamburg, 2014-03-13

Type Approval Symbol



Germanischer Lloyd

Olaf Drews

Christian Kaemmer